



BRILL® Mixed Viscosity Table

12.5W-40 × 17.5W-50

12.5W-40	17.5W-50	Viscosity(40°C)	Viscosity(100°C)	Mixed Viscosity Grade
100%	0%	88.3	13.4	12.5W-40
95%	5%	90.5	13.7	12.5W-40
90%	10%	92.7	14.0	12.5W-40
85%	15%	95.0	14.3	12.5W-40
80%	20%	97.4	14.5	12.5W-40
75%	25%	99.8	14.8	12.5W-40
70%	30%	102.2	15.2	12.5W-45
65%	35%	104.7	15.5	12.5W-45
60%	40%	107.3	15.8	15W-45
55%	45%	109.9	16.1	15W-45
50%	50%	112.6	16.4	15W-45
45%	55%	115.4	16.8	15W-45
40%	60%	118.2	17.1	15W-45
35%	65%	121.0	17.5	15W-45
30%	70%	123.9	17.8	15W-45
25%	75%	126.9	18.2	15W-45
20%	80%	130.0	18.6	17.5W-50
15%	85%	133.1	18.9	17.5W-50
10%	90%	136.3	19.3	17.5W-50
5%	95%	139.6	19.7	17.5W-50
0%	100%	142.9	20.1	17.5W-50

Unit for Viscosity mm²/S